

黏度杯

ASTM/ISO/DIN/JIS Standards Zahn/Ford/DIN Cup | NK-2

規格	號數	底部孔徑	測定範圍 Zahn秒數
ASTM Zahn Cup	#1	Ø1.93mm	60 cst max. 約35...80sec
	#2	Ø2.69mm	約20...250 cst 約20...80秒
	#3	Ø3.86mm	約100...800 cst 約20...80秒
	#4	Ø4.39mm	約200...1200 cst 約20...80秒
	#5	Ø 5.41mm	約400...1800 cst 約20...80秒

符合ASTM D1084/D4212規範、不鏽鋼製、容量約44ml



規格	號數	底部孔徑	測定範圍
JIS Zahn Cup	#2	Ø2mm	約20...85 cst
	#3	Ø3mm	約35...200 cst
	#4	Ø4mm	約180...600 cst
	#5	Ø5mm	約250...1000 cst
	#6	Ø6mm	約300...1500 cst
	#7	Ø7mm	約600...2000 cst

符合JIS規範、全長300mm、容量約45ml



黏度杯架*

規格	號數	底部孔徑	符合規範
ASTM 福特杯	ZFC 3010.1	Ø1.90mm	ASTM
	ZFC 3010.2	Ø2.53mm	
	ZFC 3010.3	Ø3.40mm	
	ZFC 3010.4	Ø4.12mm	
	ZFC 3010.5	Ø5.20mm	
DIN 黏度杯	ZFC 3011.4	Ø4mm	DIN
ISO 黏度杯	ZFC 3013.3	Ø3mm	ASTM DIN ISO EN
	ZFC 3013.4	Ø4mm	
	ZFC 3013.5	Ø5mm	
	ZFC 3013.6	Ø6mm	
ISO 附把黏度杯	ZFC 3014.3	Ø3mm	ASTM DIN ISO EN
	ZFC 3014.4	Ø4mm	
	ZFC 3014.5	Ø5mm	
	ZFC 3014.6	Ø6mm	
DIN 附把黏度杯	ZFC 3012.4	Ø4mm	DIN
ASTM 附把福特杯	ZFC 3015.4	Ø4.12mm	ASTM

耐酸鹼陽極處理鋁合金製(皆為鋁合金原色)



附把黏度杯



不鏽鋼腳架*




恆溫腳架*



岩田杯
NK-2

日本IWATA製



若需「原廠校正報告」請於訂購時註明
此外，凡加註「*」號者，皆為選購品。